

FUNZIONE

Apertura esterna con chiave d'emergenza, moneta, cacciavite, o qualsiasi attrezzo simile. Pomolo interno con bottone che aziona il segnalatore di occupato se utilizzato.

Con dispositivo di emergenza per lo sbloccaggio automatico.

FUNCTION

Unlocked from outside by emergency key, coin, screwdriver or any other similar tool. Inside knob with button acting on occupancy indicator if provided.

With emergency device for automatic release.

F12	12/FORMA senza scrocco senza controbordo	12/FORMA without latch, without striking plate
-----	--	--

FINITURE

26	Cromo lucido (US26)
6D	Cromo opaco (US26D)
15	Nickel opaco (US15)
NA	Verniciato argento
NE	Polimero nero

FINISHES

	Polish chrome (US26)
	Matt chrome (US26D)
	Matt nickel (US15)
	Silver coating
	Polymer black

SCROCCO

S	Senza scrocco
T7	TB-60 entrata mm 60 (standard)
T8	TB-70 entrata mm 70
T9	TB-80 entrata mm 80
A6	TB-127 entrata mm 127
A7	TBA-60 antiscasso, entrata mm 60
A8	TBA-70 antiscasso, entrata mm 70
o6	TBA-80 antiscasso, entrata mm 80
o7	TB-060 bordo in acciaio, entrata mm 60
o8	TB-070 bordo in acciaio, entrata mm 70
	TB-080 bordo in acciaio, entrata mm 80

TUBULAR LATCH

	Without tubular latch
	TB-60 backset 2 23/64" (standard)
	TB-70 backset 2 3/4"
	TB-80 backset 3 5/32"
	TB-127 backset 5 1/64"
	TBA-60 security device, backset 2 23/64"
	TBA-70 security device, backset 2 3/4"
	TBA-80 security device, backset 3 5/32"
	TB-060 steel edge, backset 2 23/64"
	TB-070 steel edge, backset 2 3/4"
	TB-080 steel edge, backset 3 5/32"

BORDO SCROCCO

	Quadro
T	Tondo

LATCH FOREND

	Squared
	Round

Larghezza mm 22

Width 55/64"

SPESSORI PORTE

	mm 32 ÷ 60
+	mm 60 ÷ 70
>	> mm 70

DOOR THICKNESS

	1 17/64" ÷ 2 23/64"
	2 23/64" ÷ 2 3/4"
	> 2 3/4"

CONTROBORDI

C	Senza controbordo
	P875 quadro
T	P875/T arrotondato
1	P896 rifilato
1T	P896/T rifilato arrotondato
g1	P1291/R nylon nero regolabile

STRIKING PLATE

	Without striking plate
	P875 square
	P875/T round-edge
	P896 without forend
	P896/T without forend, round-edge
	P1291/R adjustable, black nylon

BEST SELLER

F12	NA	SC					
-----	----	----	--	--	--	--	--

esterno
outside

interno
inside

