

FUNZIONE

Pomolo esterno senza pulsante con piastra di sicurezza.
Apertura solo con chiave.
Pulsante interno sempre azionabile.

FUNCTION

Outside knob without push-button, with security plate.
Unlocked only from outside by key.
Inside push-button for free passage.

N14 14/NOVA senza scrocco senza controbordo

14/NOVA without latch, without striking plate

FINITURE

BO	Verniciato bianco	White coating
NA-GR	Verniciato argento	Silver coating
NE	Verniciato nero	Black coating
3	Ottone lucido (US3)	Polish brass (US3)
4	Ottone satinato (US4)	Satin brass (US4)
26	Ottone cromo lucido (US26)	Polish chrome brass (US26)
6D	Ottone cromo satinato (US26D)	Satin chrome brass (US26D)
2B	Acciaio inox satinato	Satin stainless steel

FINISHES

Adatto per FGLA

Suitable to FGLA

SCROCCO

S	Senza scrocco	Without tubular latch
TB-60	entrata mm 60 (standard)	TB-60 backset 2 23/64" (standard)
TB-70	entrata mm 70	TB-70 backset 2 3/4"
TB-80	entrata mm 80	TB-80 backset 3 5/32"
T9	TB-127 entrata mm 127	TB-127 backset 5 1/64"
A6	TBA-60 antiscasso, entrata mm 60	TBA-60 security device, backset 2 23/64"
A7	TBA-70 antiscasso, entrata mm 70	TBA-70 security device, backset 2 3/4"
A8	TBA-80 antiscasso, entrata mm 80	TBA-80 security device, backset 3 5/32"
o6	TB-060 bordo in acciaio entrata mm 60	TB-060 steel edge, backset 2 23/64"
o7	TB-070 bordo in acciaio, entrata mm 70	TB-070 steel edge, backset 2 3/4"
o8	TB-080 bordo in acciaio, entrata mm 80	TB-080 steel edge, backset 3 5/32"

TUBULAR LATCH

BORDO SCROCCO

	Quadro	Squared
T	Tondo	Round

LATCH FOREND

Larghezza mm 22

Width 55/64"

CIFRATURE

	KD chiavi differenti	keyed differently
A	KA chiavi uguali	keyed alike
M	MK chiave maestra	master key
G	GMK chiave maestra generale	general master key
K	GGMK chiave gran maestra generale	grand general master key

KEY-CHANGES

SPESSORI PORTE

	mm 32 ÷ 60	1 17/64" ÷ 2 23/64"
+	mm 60 ÷ 70	2 23/64" ÷ 2 3/4"
>	> mm 70	> 2 3/4"

DOOR THICKNESS

CONTROBORDI

C	Senza controbordo	Without striking plate
	P875 standard, quadro	P875 standard, squared
T	P875/T arrotondato	P875/T round-edge
1	P896 rifilato	P896 without forend
1T	P896/T rifilato, arrotondato	P896/T without forend, round-edge
91	P1291/R nylon nero regolabile	P1291/R adjustable, black nylon

STRIKING PLATE

esterno
outside

interno
inside

